


UTILIZZATE PRINCIPALMENTE NEI TORNİ CON Lâ€™OBIETTIVO DI
STABILIZZARE I PEZZI LUNGI E SOTTILI, PIÙ SOGGETTI ALLA
FLESSIONE O..



€190,00



Cono morse

A	CM 2 L2 39 mm - D2-D3 16 mm - $\hat{I} \pm 60^\circ$ mm
B	L2 35,5 mm - D2-D3 16 mm - $\hat{I} \pm 75^\circ$ mm
C	L2 33 mm - D2-D3 16 mm - $\hat{I} \pm 90^\circ$ mm
D	L2 46 mm - D2-D3 16 mm - $\hat{I} \pm 60^\circ$ mm
E	L2 40 mm - D2-D3 25 mm / 10 mm - $\hat{I} \pm 60^\circ$ mm
F	L2 36 mm - D2-D3 16 mm / 10 mm - $\hat{I} \pm 60^\circ$ mm
G	L2 39 mm - D2-D3 20 mm / 16 mm - $\hat{I} \pm 60^\circ$ mm

Max rpm 5000 g/min

Portata max 45 kg

Peso lordo 1,32 kg

Dimensioni imballo 305x165x70h mm

Codice EAN 8012667244682



Valigetta



Temprato



9 Pcs



Acciaio



Rettificato